## IN THE CLAIMS:

The text of all pending claims, (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with <u>underlining</u> and deleted text with <u>strikethrough</u>. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered).

Please AMEND claims 1 and 17 in accordance with the following:

1. (currently amended) A method for processing state information in a communication system by way of a management network having a number of management levels, comprising:

transmitting state information between an agent of one management level and a manager of a next-higher management level for a state realignment upon request of said manager;

sending, by said manager, a request message for performing said state realignment to said agent;

checking, by said agent, said state information with regard to deviations from a normal state; and

sending, by said agent, changes in said state information to said manager in one or more successive messages in response to the request message, only selected state information indicating the deviations from the normal state.

- 2. (previously presented) The method as claimed in claim 1, further comprising the step of utilizing state attributes selected from the group consisting of an operational state, an administrative state, and a usage state as state information.
- 3. (previously presented) The method as claimed in claim 2, further comprising the step of defining said normal state by predetermined values for said state attributes selected from the group consisting of said operational state, said administrative state, and said usage state.
- 4. (previously presented) The method as claimed in claim 1, further comprising the step of utilizing state attributes for characterizing an operational readiness, manageability and use of a resource supported by said agent in said communication system as state information.

- 5. (previously presented) The method as claimed in claim 1, further comprising the step of utilizing status attributes, which specify for a resource supported by said agent in said communication system whether it is in an unknown state, in an alarmed state or in a state availability, as state information.
- 6. (previously presented) The method as claimed in claim 1, further comprising the step of:

sending, by said manager in said request message, a correlation information item for a correlation of said respective request with messages containing changed state information received by said agent.

7. (previously presented) The method as claimed in claim 1, further comprising the step of:

sending, by said agent in a message for starting said state realignment, a correlation information item for correlating the messages containing changed state information subsequently sent with said state realignment started in each case.

- 8. (previously presented) The method as claimed in claim 7, further comprising the step of sending said correlation information generated by said agent in said message or messages containing said changed state information.
- 9. (previously presented) The method as claimed in claim 1, further comprising the steps of:

sending, by said manager, a parameter to said agent; and controlling, by said manager, said state realignment in dependence on said parameter.

10. (previously presented) The method as claimed in claim 1, further comprising the steps of:

sending, by said manager, a parameter; automatically initiating said state realignment by said agent, utilizing said parameter.

11. (previously presented) The method as claimed in claim 10, further comprising the step of providing a parameter by said manager with a parameter value which specifies a starting time for said automatic state realignment.

- 12. (previously presented) The method as claimed in claim 10, further comprising the step of providing a parameter by said manager with a parameter value which specifies an end time for said automatic state realignment.
- 13. (previously presented) The method as claimed in claim 10, further comprising the step of providing a parameter by said manager, a parameter with a parameter value which specifies a time interval for a repetition of said automatic state realignment.
- 14. (previously presented) The method as claimed in claim 9, further comprising the step of providing, by said manager, a parameter with a parameter value which characterizes resources for which changed state information must be transmitted by said agent.
- 15. (previously presented) The method as claimed in claim 9, further comprising the step of providing, by said manager, a parameter with a parameter value that permits interruption of a running state realignment.
- 16. (previously presented) The method as claimed in claim 9, further comprising the step of sending, by said manager, said parameter to said agent in said request message.
- 17. (currently amended) A communication system for processing state information in a management network having a number of management levels, comprising:

an agent of a management level; and

a manager of a next-higher management level sending a request message for performing state realignment to said agent, said agent checking state information with regard to deviations from a normal state and sending changes in said only selected state information indicating the deviations from the normal state to said manager in one message or successive messages upon receiving in response to the request message.

18. (previously presented) The communication system as claimed in claim 17, wherein state attributes are provided selected from the group consisting of an operational state, an administrative state, and a usage state as state information.

- 19. (previously presented) The communication system as claimed in claim 18, in which the normal state is defined by values for said state attributes selected from the group consisting of an operational state, an administrative state, a usage state, an unknown state, an alarm status, and an available status.
- 20. (previously presented) The communication system as claimed in claim 17, wherein state attributes are provided for characterizing an operational readiness, a manageability and a use of a resource supported by said agent in said communication system as state information.
- 21. (previously presented) The communication system as claimed in claim 17, wherein status attributes, which specify for a resource supported by said agent in said communication system whether it is in an unknown state, in an alarm state or in a state of availability, are provided as state information.
- 22. (previously presented) The communication system as claimed in claim 17, wherein said state realignment can be controlled by said facilities in said manager in dependence on at least one parameter sent to said agent.
- 23. (previously presented) The communication system as claimed in claim 17, wherein said facilities in said manager send a parameter permitting said state realignment to be automatically initiated by said agent.
- 24. (previously presented) The method as claimed in claim 1, further comprising the step of utilizing state attributes selected from the group consisting of an unknown state, an alarm status, and an available status as state information.
- 25. (previously presented) The method as claimed in claim 24, further comprising the step of defining said normal state by predeterminable values for said state attributes selected from the group consisting of said unknown state, said alarm status, and said available status.
- 26. (previously presented) The method as claimed in claim 10, further comprising the step of providing, by said manager, a parameter with a parameter value which characterizes resources for which changed state information must be transmitted by said agent.

Serial No. 09/700,093

- 27. (previously presented) The method as claimed in claim 10, further comprising the step of providing, by said manager, a parameter with a parameter value that permits interruption of a running state realignment.
- 28. (previously presented) The method as claimed in claim 10, further comprising the step of sending, by said manager, said parameter to said agent in said request message.
- 29. (previously presented) The communication system as claimed in claim 17, wherein state attributes are provided selected from the group consisting of an unknown state, an alarm status, and an available status as state information.